352 19,6M REACH



Rather have the digital version? Go to: WWW.VANTUNEN.NL/RENTAL

EXCAVATOR 'SPECIAL' LRELONG REACH



OVERVIEW

"Load more, make more"

The new Van Tunen - 352 with a 19.6m reach - is built to take on your up-close and far-out excavating tasks. Where the real power comes in is through the integrated engine, hydraulic, and work tool systems. You can move tons of material - literally - every hour, on the hour, all day long with a great deal of speed, precision, and efficiency.

PORTFOLIO



 $\label{thm:construction} Under carriage is designed for High-Impact and High-Travel Applications, Like Mining and Heavy Construction. This model is equipped with 900mm tracked shoes.$

ATTACHMENTS



BUCKET

- HD GP bucket
- Skeleton buckets
- Ditch cleaning buckets
- Size: ± 1.2 ~ 2.0m3

GRAB

- Closed (environmental) or regular
- Size: ± 1.2 ~ 2.0m3



ORANGE PEEL GRAB

- Closed (environmental) or regular
- Size: ± 1.2 ~ 1.5m³



EXTENDER (HYDRAULIC)

Please note that we can extend the reach of the excavator for your project needs. Same as for all our attachments, we build or customize all these items at our Van Tunen yard. Please ask us for the posibilities.

FACTS & FIGURES



SPECIALTIES

- Technical Support Van Tunen
- Safety check valves on boom & stick cilinders
- Medium pressure function (rotator)
- High Presure hydraulic function hamer / shear
- · GPS / Survey on request

GENERAL INFORMATION



| INFO | SPECS |
|-----------------------------|----------------|
| Engine power | 304KW 413hp |
| Boom length | ± 11.5m |
| Stick length | ± 8.5m |
| Lifting capacity full reach | ± 6.5tons |
| Fuel consumption | ± 25-32 ltr/hr |
| Production | Contact us |


SHIPPING INFORMATION



| TOOL | SPECS |
|---------------------------|------------------------|
| Shipping height | ± 3.5m |
| Shipping Length | ± 16.4m |
| Max. width (900mm tracks) | ± 4.2m |
| Ground clearance | ± 0.71m |
| Ground pressure | ± 6.1N/cm ³ |
| Max. weight | ± 59.4 tons |
| | |

DIMENSIONS

Shipping Module dimensions and weights. All dimensions are approximate.



| ←──8─── | ←──5 ──── |
|--|---------------------|
| 1 Shipping Height* | 3530 mm |
| 2 Shipping Length | 16 460 mm |
| 3 Tail Swing Radius | 3760 mm |
| 4 Length to Center of Rollers | 4340 mm |
| 5 Track Length | 5380 mm |
| 6 Ground Clearance (including shoe lug height) | 710 mm |
| Ground Clearance (not including shoe lug height) | 740 mm |
| 7 Track Gauge | |
| Expanded | 3720 mm |
| Retracted | 3220 mm |
| 8 Transport Width (expanded) | |
| 600 mm Shoes | 4320 mm |
| 750 mm Shoes | 4470 mm |
| 900 mm Shoes | 4620 mm |
| Transport Width (retracted) | |
| 600 mm Shoes | 3820 mm |
| 750 mm Shoes | 3970 mm |
| 900 mm Shoes | 4120 mm |
| 9 Cab Height | 3390 mm |
| 10 Counterweight Clearance** | 1450 mm |
| Bucket Type | GD |
| Bucket Capacity | 0.93 m ³ |
| Bucket Tip Radius | 1573 mm |
| | |


*Including shoe lug height.

Dimensions may vary depending on bucket selection.

EXCAVATOR SPECIFICATIONS

WORKING RANGES

All dimensions are approximate.



SAFETY FIRST - QHSE



A SAFE, QUIET CAB

The ROPS cab provides you with a safe working environment. It also contributes to your comfort because it's attached to a reinforced frame with special viscous mounts that limit vibration and unnecessary sound. Add in special roof lining and sealing and you have a cab that's as quiet inside as any of today's top pickup trucks.

SECURE CONTACT POINTS

Multiple large steps get you into the cab as well as a leg up to the compartments. Extended hand and guard rails allow you to safely climb to the upper deck. Anti-skid plates reduce your slipping hazards in all types of weather conditions, and they can be removed for cleaning.

GREAT VIEWS

Ample glass gives you excellent visibility out front and to the side, and the standard rearview camera gives you a clear field of view behind the machine through the cab monitor. The available split-configuration windshield features an upper window with handles that make it easy to slide and store above you and a lower window that can be removed and stored on the inside wall of the cab. The large skylight also serves as an emergency exit and provides you with enhanced overhead visibility.



SMART LIGHTING

Halogen lights provide plenty of illumination, and the cab and boom lights can be programmed to stay on for up to 90 seconds after the engine has been turned off to help you safely exit the machine. Optional High Intensity Discharge (HID) lights are available for enhanced night-time visibility.



REQUIRE THIS MACHINE FOR YOUR PROJECT?

Please contact us for a competitive quotation or for further information about our customized solutions. Feel free to give us a call +31 251 26 44 44, send us an e-mail info@vantunen.nl or visit www.vantunen.nl

Experts in coastal development, earthmoving, rock works and mining

Van Tunen provides worldwide rental of heavy earthmoving equipment and technical project support services for the dredging, earthmoving and mining industry as well as the maritime sector. From harbour improvement to coastal protection, from pipeline works to demolition, depend on our team for solid advice, made-to-measure solutions and prompt support.

Get to know us, please visit: www.vantunen.nl

